Model: 352½MM

Cast Bronze Sil-Braze Ends Y Strainers Sizes: 1/4" - 4" (8 - 100mm)

| Pressure/Temperature - Non-Shock | Model | Material | Rating | 250psi @ 425°F | 17.2 bar @ 218°C

352½**M** Sil-Braze **Class 125**



Typical Service

 Used to strain foreign matter from pipelines and provide economical protection for costly pumps, meters, valves, and other similar mechanical equipment

Features

- Machined seats in both body and cap align and lock the screen in place to stop sediment bypass.
- 352-1/2 conforms to Military specifications
- 352-1/2 conforms to the latest revision of BuShip Drawing 80064-810-841499.
- All sizes of 352-1/2 are furnished grooved less rings.

Self-Cleaning

• Self-cleaning is accomplished by opening the plug or valve connected to the blowoff outlet

Blowoff Outlets

- · Outlets are NPT tapped
- · Sizes of tapping are specified on next page
- · Not normally furnished with plug. Plug is available, specify with order.
- BuShip Drawing strainers are supplied without blowoff outlets.

Capacity

- · Generously proportioned bodies
- Open Area Ratio much greater than pipe size, ensuring low pressure drop.

Screens

		STANDARD (V	STANDARD (WATER)		STEAM RECOMENDATION		
MODEL	SIZES	MATERIAL	OPENING	MATERIAL	OPENING		
352-1/2M	1/4" - 2"	304SS	20 mesh	304SS	.033 perf		
352-1/2M	21/2" - 4"	304SS	.062 perf	304SS	.033 perf		

Materials

	3521/2MM
Body	Bronze ASTM B61
Сар	Bronze ASTM B61
Screen	304SS
Gasket	Copper

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative




Pressure Drop

See Pressure Drop Charts in Technical Data Section of the Mueller Steam Specialty Engineering binder.

Dimensions and Weights

SI	ZE			DIMENSIONS						WEIGHT	
		A B		3	C (NPT)		D Screen Removal				
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
352 ¹ / ₂ N	352½MM										
1/4	8	2 9/16	65	11//8	48	1/8	3	23/4	70	.75	.34
3/8	10	2 %16	65	111/8	48	1/8	3	23/4	70	.75	.34
1/2	15	2 ¹⁵ / ₁₆	75	21//8	54	1/8	3	3	76	1	.45
3/4	20	33/8	86	2 %16	65	1/4	6	4	102	1.75	.79
1	25	41/8	105	31//8	79	1/4	6	41/2	114	2.5	1.1
11/4	32	4 ¹³ / ₁₆	122	31//8	90	3/8	10	5½	140	4.25	1.9
11/2	40	5 3/8	137	43/16	122	1/2	15	6½	165	5.5	2.5
2	50	65/8	168	5 %	137	3/4	20	81/4	210	8.25	3.7
2 ½	65	7 ½	200	61/2	165	1	25	10	254	15.5	7
3	80	113/4	298	7	178	1	25	10½	267	36	16
4	100	15 ³ ⁄ ₁₆	386	11%	289	Blind	Cover	16	406	90	41



Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.

